

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## SECTION 1: Identification

### 1.1 Product identifier

Trade name **Cerakote Headlight Step 3: Ceramic Clear Coating**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer use (private households)  
Automotive Restoration

### 1.3 Details of the supplier of the safety data sheet

NIC Industries, Inc  
7050 6th St.  
White City Oregon 97503  
United States

Telephone: 866-774-7628  
e-mail: sds@nicindustries.com  
Website: www.nicindustries.com

### 1.4 Emergency telephone number

Emergency information service 1-800-633-8253 (USA & Canada) or 001-1-801-629-0667 (International)

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

## SECTION 2: Hazard(s) identification

### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Section | Hazard class                      | Category | Hazard class and category | Hazard statement |
|---------|-----------------------------------|----------|---------------------------|------------------|
| A.10    | Acute toxicity (oral)             | 4        | Acute Tox. 4              | H302             |
| A.2     | Skin corrosion/irritation         | 1B       | Skin Corr. 1B             | H314             |
| A.3     | Serious eye damage/eye irritation | 1        | Eye Dam. 1                | H318             |
| A.4S    | Skin sensitization                | 1        | Skin Sens. 1              | H317             |
| B.6     | Flammable liquid                  | 2        | Flam. Liq. 2              | H225             |

For full text of abbreviations: see SECTION 16.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word

**DANGER**

- Pictograms

GHS02, GHS05, GHS07



- Hazard statements

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapor.       |
| H302 | Harmful if swallowed.                    |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction.     |

- Precautionary statements

|                |  |
|----------------|--|
| P210           | Keep away from heat/sparks/open flames/hot surfaces. No smoking.   |
| P233           | Keep container tightly closed.   |
| P240           | Ground/bond container and receiving equipment.   |
| P241           | Use explosion-proof electrical/ventilating/lighting equipment.   |
| P242           | Use only non-sparking tools.   |
| P243           | Take precautionary measures against static discharge.  |
| P260           | Do not breathe dusts or mists.   |
| P270           | Do not eat, drink or smoke when using this product.  |
| P272           | Contaminated work clothing must not be allowed out of the workplace.   |
| P280           | Wear protective gloves/eye protection/face protection.   |
| P301+P330+P331 | If swallowed: Rinse mouth. Do NOT induce vomiting.   |
| P302+P352      | If on skin: Wash with plenty of water.   |
| P303+P361+P353 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | If inhaled: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a poison center/doctor.   |
| P321           | Specific treatment (see on this label).  |
| P363           | Wash contaminated clothing before reuse.   |
| P370+P378      | In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.  |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container to industrial combustion plant.  |

- Hazardous ingredients for labelling

Ambient Cure Refractory Resin

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## 2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

| Name of substance             | Identifier             | Wt%       |
|-------------------------------|------------------------|-----------|
| Ambient Cure Refractory Resin | CAS No<br>Trade Secret | 25 - < 50 |
| Rheology Modifier             | CAS No<br>Trade Secret | 25 - < 50 |
| Leveling Agent                | CAS No<br>Trade Secret | 25 - < 50 |

\*\* Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret."

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## 4.3 Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Dry extinguishing powder, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet, Water spray

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

This information is not available.

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|                |                       |
|----------------|-----------------------|
| Physical state | Moistened towelette   |
| Color          | White                 |
| Particle       | Not relevant (liquid) |
| Odor           | Ammoniacal            |

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## Other safety parameters

|   |                   |
|---|-------------------|
| pH (value)                              | Not determined    |
| Melting point/freezing point            | Not determined    |
| Initial boiling point and boiling range | 100.5 °C          |
| Flash point                             | 0 °C              |
| Evaporation rate                        | Not determined    |
| Flammability (solid, gas)               | Not relevant      |
| Vapor pressure                          | 5,500 Pa at 25 °C |
| Density                                 | Not determined    |
| Vapor density                           | Not available     |
| Relative density                        | Not available     |
| Solubility(ies)                         | Not determined    |

## Partition coefficient

|                             |                |
|-----------------------------|----------------|
| - n-octanol/water (log KOW) | Not available  |
| Auto-ignition temperature   | 340 °C         |
| Viscosity                   | Not determined |
| Explosive properties        | None           |
| Oxidizing properties        | None           |

## 9.2 Other information

|  |  |
|--|--|
| Temperature class (USA, acc. to NEC 500) | T2 (maximum permissible surface temperature on the equipment: 300°C) |
|--|--|

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition. Reacts with water.

If heated:

Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers.

### 10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Oral 789.5 mg/kg

Acute toxicity estimate (ATE) of components of the mixture

| Name of substance             | CAS No       | Exposure route | ATE        |
|-------------------------------|--------------|----------------|------------|
| Ambient Cure Refractory Resin | Trade Secret | oral           | >300 mg/kg |



# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

- Skin corrosion/irritation  
Causes severe skin burns and eye damage.
- Serious eye damage/eye irritation  
Causes serious eye damage.
- Respiratory or skin sensitization  
May cause an allergic skin reaction.
- Germ cell mutagenicity  
Shall not be classified as germ cell mutagenic.
- Carcinogenicity  
Shall not be classified as carcinogenic.
- Reproductive toxicity  
Shall not be classified as a reproductive toxicant.
- Specific target organ toxicity - single exposure  
Shall not be classified as a specific target organ toxicant (single exposure).
- Specific target organ toxicity - repeated exposure  
Shall not be classified as a specific target organ toxicant (repeated exposure).
- Aspiration hazard  
Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

| Aquatic toxicity (acute) of components of the mixture |              |          |           |                       |               |
|---|--------------|----------|-----------|-----------------------|---------------|
| Name of substance                                     | CAS No       | Endpoint | Value     | Species               | Exposure time |
| Ambient Cure Refractory Resin                         | Trade Secret | LC50     | 57.1 mg/l | Zebra fish            | 96 h          |
| Rheology Modifier                                     | Trade Secret | LC50     | >19 µg/l  | Fish                  | 96 h          |
| Rheology Modifier                                     | Trade Secret | EC50     | >20 µg/l  | Aquatic invertebrates | 48 h          |
| Rheology Modifier                                     | Trade Secret | ErC50    | >9.4 µg/l | Algae                 | 72 h          |
| Leveling Agent  | Trade Secret | LC50     | 0.46 mg/l | Fish                  | 96 h          |

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

Aquatic toxicity (chronic) of components of the mixture

| Name of substance | CAS No       | Endpoint | Value      | Species               | Exposure time |
|-------------------|--------------|----------|------------|-----------------------|---------------|
| Rheology Modifier | Trade Secret | EC50     | >15 µg/l   | Aquatic invertebrates | 21 d          |
| Leveling Agent    | Trade Secret | EC50     | 0.3 mg/l   | Aquatic invertebrates | 21 d          |
| Leveling Agent    | Trade Secret | LC50     | 0.45 mg/l  | Aquatic invertebrates | 21 d          |
| Leveling Agent    | Trade Secret | ErC50    | >0.55 mg/l | Algae                 | 95 h          |

**12.2 Persistence and degradability**

Data are not available.

**12.3 Bioaccumulative potential**

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Endocrine disrupting properties**

None of the ingredients are listed.

**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## SECTION 14: Transport information

### 14.1 UN number

|           |         |
|-----------|---------|
| DOT       | UN 3175 |
| IMDG-Code | UN 3175 |
| ICAO-TI   | UN 3175 |

### 14.2 UN proper shipping name

|  |   |
|--|---|
| DOT                                    | Solids containing flammable liquid, n.o.s.    |
| IMDG-Code                              | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.    |
| ICAO-TI                                | Solids containing flammable liquid, n.o.s.    |
| Technical name (hazardous ingredients) | Leveling Agent, Ambient Cure Refractory Resin |

### 14.3 Transport hazard class(es)

|           |     |
|-----------|-----|
| DOT       | 4.1 |
| IMDG-Code | 4.1 |
| ICAO-TI   | 4.1 |

### 14.4 Packing group

|           |    |
|-----------|----|
| DOT       | II |
| IMDG-Code | II |
| ICAO-TI   | II |

### 14.5 Environmental hazards

|   |   |
|---|---|
| Environmentally hazardous substance (aquatic environment) | hazardous to the aquatic environment<br>Rheology Modifier |
|---|---|

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### **Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

|  |  |
|--|--|
| Particulars in the shipper's declaration | UN3175, Solids containing flammable liquid, n.o.s., 4.1, II, environmentally hazardous |
| Danger label(s)                          | 4.1, fish and tree   |



|                       |  |
|-----------------------|--|
| Environmental hazards | YES (hazardous to the aquatic environment) |
|-----------------------|--|

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

|                         |                        |
|-------------------------|------------------------|
| Special provisions (SP) | 47, IB6, IP2, T3, TP33 |
| ERG No                  | 133                    |
| Remarks                 |                        |

Special Provision 47: Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, for single packagings, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to this subchapter provided there is no free liquid in the packet or article.

**International Maritime Dangerous Goods Code (IMDG) - Additional information**

|                  |  |
|------------------|--|
| Marine pollutant | YES (hazardous to the aquatic environment) (Rheology Modifier) |
| Danger label(s)  | 4.1, fish and tree   |



|                          |          |
|--------------------------|----------|
| Special provisions (SP)  | 216, 274 |
| Excepted quantities (EQ) | E2       |
| Limited quantities (LQ)  | 1 kg     |
| EmS                      | F-A, S-I |
| Stowage category         | B        |

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

|                       |  |
|-----------------------|--|
| Environmental hazards | YES (hazardous to the aquatic environment) |
| Danger label(s)       | 4.1  |



|                          |      |
|--------------------------|------|
| Special provisions (SP)  | A46  |
| Excepted quantities (EQ) | E2   |
| Limited quantities (LQ)  | 5 kg |

Remarks

Special Provision A46: Mixtures of solids which are not subject to these Instructions and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, providing there is no free liquid visible at the time the substance is packaged and, for single packagings, the packaging must pass a leakproofness test at the Packing Group II level. Sealed packets and articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Instructions provided there is no free liquid in the packet or articles.

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

##### Toxic Substance Control Act (TSCA)

All ingredients are listed

##### Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

None of the ingredients are listed.

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

None of the ingredients are listed.

##### Clean Air Act

None of the ingredients are listed.

##### Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

None of the ingredients are listed.

- Hazardous Substances List (MN-ERTK)

None of the ingredients are listed.

- Hazardous Substance List (NJ-RTK)

None of the ingredients are listed.

- Hazardous Substance List (Chapter 323) (PA-RTK)

None of the ingredients are listed.

- Hazardous Substance List (RI-RTK)

None of the ingredients are listed.

##### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

None of the ingredients are listed.

##### VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact [sds@nicindustries.com](mailto:sds@nicindustries.com) for more information.

##### Industry or sector specific available guidance(s)

###### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

| Category       | Degree of hazard | Description  |
|----------------|------------------|--|
| Flammability   | 3                | Material that can be ignited under almost all ambient temperature conditions     |
| Health         | 3                | Material that, under emergency conditions, can cause serious or permanent injury |
| Instability    | 0                | Material that is normally stable, even under fire conditions                     |
| Special hazard |                  |  |

## National inventories

| Country | Inventory  | Status                         |
|---------|------------|--------------------------------|
| AU      | AICS       | Not all ingredients are listed |
| CA      | DSL        | Not all ingredients are listed |
| CA      | NDSL       | Not all ingredients are listed |
| CN      | IECSC      | Not all ingredients are listed |
| EU      | ECSI       | Not all ingredients are listed |
| EU      | REACH Reg. | Not all ingredients are listed |
| JP      | CSCL-ENCS  | Not all ingredients are listed |
| JP      | ISHA-ENCS  | Not all ingredients are listed |
| KR      | KECI       | All ingredients are listed     |
| MX      | INSQ       | Not all ingredients are listed |
| NZ      | NZIoC      | All ingredients are listed     |
| PH      | PICCS      | Not all ingredients are listed |
| TR      | CICR       | Not all ingredients are listed |
| TW      | TCSI       | All ingredients are listed     |
| US      | TSCA       | All ingredients are listed     |

### Legend

|            |   |
|------------|---|
| AICS       | Australian Inventory of Chemical Substances                             |
| CICR       | Chemical Inventory and Control Regulation                               |
| CSCL-ENCS  | List of Existing and New Chemical Substances (CSCL-ENCS)                |
| DSL        | Domestic Substances List (DSL)  |
| ECSI       | EC Substance Inventory (EINECS, ELINCS, NLP)                            |
| IECSC      | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ       | National Inventory of Chemical Substances                               |
| ISHA-ENCS  | Inventory of Existing and New Chemical Substances (ISHA-ENCS)           |
| KECI       | Korea Existing Chemicals Inventory                                      |
| NDSL       | Non-domestic Substances List (NDSL)                                     |
| NZIoC      | New Zealand Inventory of Chemicals                                      |
| PICCS      | Philippine Inventory of Chemicals and Chemical Substances (PICCS)       |
| REACH Reg. | REACH registered substances   |
| TCSI       | Taiwan Chemical Substance Inventory                                     |
| TSCA       | Toxic Substance Control Act   |

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Abbreviations and acronyms

| Abbr.         | Descriptions of used abbreviations   |
|---------------|--|
| 49 CFR US DOT | 49 CFR U.S. Department of Transportation   |
| ATE           | Acute Toxicity Estimate  |
| CAS           | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)   |
| DGR           | Dangerous Goods Regulations (see IATA/DGR)   |
| DOT           | Department of Transportation (USA)   |
| EC50          | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EINECS        | European Inventory of Existing Commercial Chemical Substances  |
| ELINCS        | European List of Notified Chemical Substances  |
| EmS           | Emergency Schedule   |
| ErC50         | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control           |
| ERG No        | Emergency Response Guidebook - Number  |
| GHS           | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations  |
| IATA          | International Air Transport Association  |
| IATA/DGR      | Dangerous Goods Regulations (DGR) for the air transport (IATA)   |
| ICAO          | International Civil Aviation Organization  |
| ICAO-TI       | Technical instructions for the safe transport of dangerous goods by air  |
| IMDG          | International Maritime Dangerous Goods Code  |
| IMDG-Code     | International Maritime Dangerous Goods Code  |
| LC50          | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval                                |
| MARPOL        | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")  |
| NLP           | No-Longer Polymer  |
| OSHA          | Occupational Safety and Health Administration (United States)  |
| PBT           | Persistent, Bioaccumulative and Toxic  |
| RTECS         | Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)  |
| VOC           | Volatile Organic Compounds   |

# Cerakote Headlight Step 3: Ceramic Clear Coating

Version number: 3.0

Revision: 04/11/2022

| Abbr. | Descriptions of used abbreviations       |
|-------|--|
| vPvB  | Very Persistent and very Bioaccumulative |

## Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text                                     |
|------|--|
| H225 | Highly flammable liquid and vapor.       |
| H302 | Harmful if swallowed.                    |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction.     |
| H318 | Causes serious eye damage.               |