

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## SECTION 1: Identification

### 1.1 Product identifier

Trade name **Cerakote Elite Series: Part A**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses **General use**

### 1.3 Details of the supplier of the safety data sheet

NIC Industries, Inc  
7050 6th St.  
White City Oregon 97503  
United States

Telephone: 866-774-7628  
e-mail: sds@nicindustries.com  
Website: www.nicindustries.com

### 1.4 Emergency telephone number

Emergency information service **1-800-633-8253 (USA & Canada) or 001-1-801-629-0667 (International)**

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

## SECTION 2: Hazard(s) identification

### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4S	Skin sensitization	1	Skin Sens. 1	H317
A.6	Carcinogenicity	1B	Carc. 1B	H350
B.6	Flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **DANGER**

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H350 May cause cancer.

- Precautionary statements

- P201 Obtain special instructions before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash it before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Ambient Curable Refractory Resin, Performance Ceramic #2, p-chlorobenzotrifluoride

## 2.3 Other hazards

Hazards not otherwise classified

- May be harmful if swallowed (GHS category 5: acutely toxic - oral).
- May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
- May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).
- Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%
p-chlorobenzotrifluoride	CAS No 98-56-6	50 - < 75
Performance Ceramic #2	CAS No Trade Secret	10 - < 25
Performance Ceramic #3	CAS No Trade Secret	10 - < 25
Performance Ceramic #1	CAS No Trade Secret	10 - < 25
Ambient Curable Refractory Resin	CAS No Trade Secret	10 - < 25
Ceramic Based Pigments and Additives	CAS No Trade Secret	10 - < 25
Cross-linking Agent	CAS No Trade Secret	5 - < 10
2-butanol	CAS No 78-92-2	1 - < 5
Chromium (III) oxide	CAS No 1308-38-9	< 1

\*\* Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret."

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

## 4.3 Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, Dry extinguishing powder, BC-powder, Carbon dioxide (CO<sub>2</sub>)

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	Performance Ceramic #1	TLV®		10						ACGIH® 2019
US	Performance Ceramic #1	PEL		15					i, dust	29 CFR 1910.1000
US	Performance Ceramic #1	REL							lowest, appx-A	NIOSH REL
US	Performance Ceramic #2	REL		10 (10 h)						NIOSH REL
US	Performance Ceramic #2	TLV®		0.1					fib/cm <sup>3</sup> , CA-10	ACGIH® 2019
US	Performance Ceramic #2	PEL		15					i, dust	29 CFR 1910.1000
US	Performance Ceramic #2	TLV®		10					i, noAsb_le ss1Sil, non fib.	ACGIH® 2019
US	Performance Ceramic #2	REL		5 (10 h)					r	NIOSH REL
US	Performance Ceramic #2	PEL		5					r, dust	29 CFR 1910.1000
US	Performance Ceramic #2	TLV®		3					r, noAsb_le ss1Sil, non fib.	ACGIH® 2019
US	2-Butanol	TLV®	100							ACGIH® 2019
US	2-Butanol	PEL (CA)	100	305						Cal/OSHA PEL
US	2-Butanol	REL	100 (10 h)	305 (10 h)	150	455				NIOSH REL
US	2-Butanol	PEL	150	450						29 CFR 1910.1000

**Notation**

appx-A  
CA-10

Ceiling-C  
dust

NIOSH Potential Occupational Carcinogen (Appendix A)  
Respirable fibers: length > 5µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination.  
ceiling value is a limit value above which exposure should not occur  
as dust

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

**Notation**

fib/cm <sup>3</sup>	fibers/cm <sup>3</sup>
i	inhalable fraction
lowest	exposure by all routes should be carefully controlled to levels as low as possible
noAsb_less1S	contains no asbestos and less than 1% free crystalline silica
il	
non fib.	non fibrous
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance**

Physical state	Liquid
Color	Various
Odor	Ammoniacal

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## Other safety parameters

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	>133.8 °C
Flash point	39 °C
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid)
Vapor pressure	0.07 Pa at 25 °C
Density	Not determined
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Not determined

## Partition coefficient

- n-octanol/water (log KOW)	Not available
Auto-ignition temperature	230 °C
Viscosity	Not determined
Explosive properties	None
Oxidizing properties	None

## 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)
--	---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition.



# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

No known hazardous reactions.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**10.5 Incompatible materials**

Oxidizers. Strong acids. Water. Alkalines.

**10.6 Hazardous decomposition products**

Chlorine-containing gases, fluorine-containing gases may be produced in products containing p-chlorobenzotrifluoride. Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Hazardous combustion products: see section 5.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed, in contact with skin or if inhaled.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Ceramic Based Pigments and Additives	Trade Secret	inhalation: vapor	11 mg <sub>l</sub> /4h
Ceramic Based Pigments and Additives	Trade Secret	inhalation: dust/mist	2.3 mg <sub>l</sub> /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

**Carcinogenicity**

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	Classification	Number
Performance Ceramic #2	2A	
Performance Ceramic #1	2B	
p-chlorobenzotrifluoride	2B	

Legend

2A Probably carcinogenic to humans  
 2B Possibly carcinogenic to humans

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
p-chlorobenzotrifluoride	98-56-6	LC50	6.5 mg/l	Fish	24 h
p-chlorobenzotrifluoride	98-56-6	ErC50	>0.41 mg/l	Algae	72 h
p-chlorobenzotrifluoride	98-56-6	EC50	>0.41 mg/l	Algae	72 h
Performance Ceramic #3	Trade Secret	LC50	100 mg/l	Fish	96 h
Performance Ceramic #3	Trade Secret	EC50	>100 mg/l	Aquatic invertebrates	24 h
Performance Ceramic #2	Trade Secret	ErC50	>100 mg/l	Algae	48 h
Cross-linking Agent	Trade Secret	LC50	>100 mg/l	Fish	96 h
Cross-linking Agent	Trade Secret	EC50	>100 mg/l	Aquatic invertebrates	48 h
2-butanol	78-92-2	LC50	2,993 mg/l	Fish	96 h
2-butanol	78-92-2	EC50	308 mg/l	Aquatic invertebrates	48 h

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butanol	78-92-2	ErC50	2,029 mg/l	Algae	96 h
Chromium (III) oxide	1308-38-9	ErC50	>148.1 µg/l	Algae	72 h
Chromium (III) oxide	1308-38-9	EC50	13.3 µg/l	Algae	72 h

## Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
p-chlorobenzotrifluoride	98-56-6	EC50	242.1 mg/l	Microorganisms	30 min
Ceramic Based Pigments and Additives	Trade Secret	EC50	300.4 mg/l	Microorganisms	3 h
Chromium (III) oxide	1308-38-9	EC50	>10,000 mg/l	Microorganisms	3 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information**

**14.1 UN number**

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

**14.2 UN proper shipping name**

DOT	Paint related material
IMDG-Code	PAINT RELATED MATERIAL
ICAO-TI	Paint related material

**14.3 Transport hazard class(es)**

DOT	3
IMDG-Code	3
ICAO-TI	3

**14.4 Packing group**

DOT	III
IMDG-Code	III
ICAO-TI	III

**14.5 Environmental hazards**

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	p-chlorobenzotrifluoride

**14.6 Special precautions for user**

There is no additional information.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**

The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations**

**Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Particulars in the shipper's declaration	UN1263, Paint related material, 3, III, environmentally hazardous
Danger label(s)	3, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
-----------------------	--

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Special provisions (SP)	367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No	128
<b>International Maritime Dangerous Goods Code (IMDG) - Additional information</b>	
Marine pollutant	yes (hazardous to the aquatic environment) (p-chlorobenzotrifluoride)
Danger label(s)	3, fish and tree
Special provisions (SP)	163, 223, 367, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A
<b>International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information</b>	
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3
Special provisions (SP)	A3, A72, A192
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

#### Toxic Substance Control Act (TSCA)

All ingredients are listed

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
2-butanol	78-92-2		12/31/1986

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)  
none of the ingredients are listed

## Clean Air Act

none of the ingredients are listed

## Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
2-butanol	78-92-2		LHS		1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	References	Remarks
Performance Ceramic #2	A	
Performance Ceramic #1	A	
2-butanol	A, O	

### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	Remarks	Classifications
Performance Ceramic #2		
Performance Ceramic #1		
Chromium (III) oxide		
Chromium (III) oxide		
2-butanol		F3

### Legend

- F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Classification
Performance Ceramic #2	
Performance Ceramic #1	
Chromium (III) oxide	*, E, S

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Name of substance	Classification
2-butanol	E

Legend

- \* Any compound of this substance is also an environmental hazard
- E Environmental hazard
- S Special hazardous substance

- Hazardous Substance List (RI-RTK)

Name of substance	References
Performance Ceramic #2	T
Performance Ceramic #1	T
2-butanol	T, F

Legend

- F Flammability (NFPA®)
- T Toxicity (ACGIH®)

**California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987**

Proposition 65 List of chemicals		
Name of substance	Remarks	Type of the toxicity
Performance Ceramic #1	airborne, unbound particles of respirable size	cancer
p-chlorobenzotrifluoride		cancer

**Industry or sector specific available guidance(s)**

**NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## National inventories

Country	Inventory	Status
AU	AICS	All ingredients are listed
CA	DSL	Not all ingredients are listed
CA	NDSL	Not all ingredients are listed
CN	IECSC	All ingredients are listed
EU	ECSI	All ingredients are listed
EU	REACH Reg.	All ingredients are listed
JP	CSCL-ENCS	Not all ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	All ingredients are listed
MX	INSQ	Not all ingredients are listed
NZ	NZIoC	Not all ingredients are listed
PH	PICCS	All ingredients are listed
TR	CICR	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed

### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance

# Cerakote Elite Series: Part A

Version number: 1.0

Date of compilation: 04/07/2021

Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

## Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.