

acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

SECTION 1: Identification

1.1 Product identifier

Trade name Cerakote F-109 Storm

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Professional use

1.3 Details of the supplier of the safety data sheet

NIC Industries, Inc 7050 6th St. White City Oregon 97503 United States

Telephone: 866-774-7628 e-mail: sds@nicindustries.com Website: www.nicindustries.com

1.4 Emergency telephone number

Emergency information service

1-800-633-8253 (USA & Canada)

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class and category code(s)

Classification acc. to GHS

Section	Hazard class		Hazard class and cat- egory	Hazard state- ment
A.2	A.2 Skin corrosion/irritation		Skin Irrit. 2	H315
A.3	Serious eye damage/eye irritation		Eye Irrit. 2A	H319
A.4S	Skin sensitization		Skin Sens. 1	H317
A.5	Germ cell mutagenicity		Muta. 2	H341
A.6	.7 Reproductive toxicity		Carc. 2	H351
A.7			Repr. 2	H361fd
A.8R			STOT SE 3	H335
B.6	Flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **WARNING**

- Pictograms

GHS07, GHS08



- Hazard statements

H227 Combustible liquid. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

- Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

p-chlorobenzotrifluoride, Ambient Curable Refractory Resin, Wetting Agent, Performance Ceramic #2

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	ldentifier	Wt%
p-chlorobenzotrifluoride	CAS No 98-56-6	50 – < 75
Ambient Curable Refractory Resin	CAS No Trade Secret	10 - < 25
Performance Ceramic #2	CAS No Trade Secret	5 – < 10
Wetting Agent	CAS No Trade Secret	1-<5
Performance Ceramic #3	CAS No Trade Secret	1-<5

Remarks

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

None.

^{**} Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret"



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry extinguishing powder, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits	Occupationa	l exposure	limit values	(Workp	lace Ex	posure	Limits)
---	-------------	------------	--------------	--------	---------	--------	---------

	•					•				
Country	Name of substance	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	Performance Ceramic #2	REL		10 (10 h)						NIOSH REL
US	Performance Ceramic #2	PEL		15					dust	29 CFR 1910.100 0
US	Performance Ceramic #2	TLV®		0.1					fib/cm³, CA-11, CA-10	ACGIH® 2024
US	Performance Ceramic #2	TLV®		10					i, non fib.	ACGIH® 2024



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	Performance Ceramic #2	REL		5 (10 h)					r	NIOSH REL
US	Performance Ceramic #2	PEL		5					r	29 CFR 1910.100 0
US	Performance Ceramic #2	TLV®		3					r, non fib.	ACGIH® 2024

Notation

CA-10 Respirable fibers: length > 5µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450 times magnifica-

tion (4-mm objective), using phase-contrast illumination.

CA-11 including whiskers

Ceiling-C ceiling value is a limit value above which exposure should not occur

dust as dust
fib/cm³ fibers/cm³
i inhalable fraction
non fib. non fibrous
r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (un-

less otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

Exhaust ventilation. General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid
Color	Characteristic
Particle	Not relevant (liquid)
Particle size	Not available
Odor	Characteristic

Other safety parameters

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	>133.8 °C at 1 atm
Flash point	39 °C
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid)
Explosive limits	Not determined
Vapor pressure	0.15 hPa at 20 °C
Density	1.43 ^g / _{cm³}
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Not determined

Partition coefficient

- n-octanol/water (log KOW)	Not available
Auto-ignition temperature	276 °C
Decomposition temperature	Not relevant

Viscosity Not determined

	- Kinematic viscosity	Not determined
ı		



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

Explosive properties	None
Oxidizing properties	None

There is no additional information

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment; 360%)
	ment: 260°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

If heated:

Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Moisture.

Hints to prevent fire or explosion

 $Use \ explosion-proof \ electrical/ventilating/lighting/equipment. \ Use \ only \ non-sparking \ tools. \ Take \ precautionary \ measures \ against \ static \ discharge.$

10.5 Incompatible materials

Oxidizers. Alcohols.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Chlorine-containing gases, fluorine-containing gases may be produced in products containing p-chlorobenzotrifluoride. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
p-chlorobenzotrifluoride	98-56-6	Dermal	>3,300 ^{mg} / _{kg}
Performance Ceramic #3	Trade Secret	Inhalation: dust/mist	>1.5 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	Classification	Number
Performance Ceramic #2	2A	
p-chlorobenzotrifluoride	2B	

Legend

Probably carcinogenic to humansPossibly carcinogenic to humans

Reproductive toxicity

Suspected of damaging the unborn child. Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/packaging disposal

Do not empty into drains. Avoid release to the environment. Contact a licensed professional waste disposal service to dispose of this material and its packaging.

Waste treatment of containers/packages

Follow all local, state, and Federal disposal regulations.

Hazardous waste code(s)

The waste code(s) should be assigned in discussion between the user and the waste disposal company.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Remarks

Cerakote F-109 Storm product does not need to be regulated for purposes of transportation due to the fact that the p-chlorobenzotrifluoride (CAS# 98-56-6) contained in the mixture does not sustain combustion. Per 49 CFR § 173.120(a)(3) of the hazardous materials regulations, liquids with a flash point greater than 35°C that do not sustain combustion according to ASTM D 4206 do not meet the definition of a Class 3 Flammable Liquid. Additionally, International Air Transport Association (IATA) Dangerous Goods Regulations section 3.3.1.3(a) states that liquids which do not sustain combustion "need not be considered as flammable" if the liquid has "passed a suitable test for combustibility" as prescribed by the UN Manual of Tests and Criteria, Part III, subsection 32.5.2. ASTM D 4206 standards are identical to the UN Manual standards; it is thus considered to be a suitable test for combustibility. For the aforementioned reasons, Cerakote F-109 Storm is not considered regulated for purposes of transportation.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

All ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

Please contact sds@nicindustries.com for more information.

- Specific Toxic Chemical Listings (EPCRA Section 313) Please contact sds@nicindustries.com for more information.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) Please contact sds@nicindustries.com for more information.

Clean Air Act

Please contact sds@nicindustries.com for more information.

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)
 None of the ingredients are listed.
- Hazardous Substances List (MN-ERTK)

Name of substance	References
Performance Ceramic #2	А

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- Hazardous Substance List (NJ-RTK)

Name of substance	Classifications
Performance Ceramic #2	

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Classification
Performance Ceramic #2	



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

- Hazardous Substance List (RI-RTK)

Name of substance	References
Performance Ceramic #2	Т

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name of substance	Remarks	Type of the toxicity
p-chlorobenzotrifluoride		cancer

VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact sds@nicindustries.com for more information.

National inventories

Country	Inventory	Status
AU	AIIC	All ingredients are listed
CA	DSL	All ingredients are listed
CN	IECSC	All ingredients are listed
EU	ECSI	All ingredients are listed
EU	REACH Reg.	All ingredients are listed
JP	CSCL-ENCS	All ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	All ingredients are listed
MX	INSQ	All ingredients are listed
NZ	NZIoC	All ingredients are listed
PH	PICCS	All ingredients are listed
TR	CICR	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed (ACTIVE)

Legend

AllC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

<u>Legend</u>

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million



acc. to 29 CFR 1910.1200 App D

Cerakote F-109 Storm

Version number: 1.0 Date of compilation: 01/13/2025

Abbr.	Descriptions of used abbreviations
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.